

## EPS Profile cylinder | Half cylinder Euro profile SY-MO











## **Product description**

The EPS Euro profile half cylinder in modular design (SY-MO) with 8-way adjustable cam is suitable for use in switching devices and in special technical doors. The cylinder can be locked from one side using the authorised keys. Potential applications are key switches for garage doors, roller shutters and activation devices.

## **Technical information**

| System                                  | EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin  |
|---|--|
| Cylinder length on the outside A in mm  | 271   31   36   41   +5  |
| Finish                                  | NI - Nickel   MS - Brass   NP - Polished Nickel   NPV - Nickel fully polished   MP - Polished brass   MPV - Brass fully polished   ML - Brass lacquered   CR - Chrome   CP - Polished chrome   CPV - Chrome fully polished   PS - Patinated black   PB - Patinated brown                           |
| Optional security features              | KZ-A – Increased plug pulling and drilling protection outside   SKG2-A – SKG ** certified outside   VDS – VdS certified  |
| Optional technical installation feature | 2GW[] - Double rear fixing for HZ   FL1 - Free wheel function   KS-A - Contact pin outside   LW[] - Free travel   NS-A - Increased wear resistance outside   SEW - Sea water protection   SW-A - Dust and weather protection outside   Z[] - Cog wheel cam   ZVS-A - Reduced cylinder body outside |
| Optional usage feature                  | TXT - Customer-specific text   |
| Accessories                             | Spray FinLube   Cylinder fixing screw  |
| Security features                       | Pin tumbler system with 5 or 6 active, spring-loaded locking elements   Features in cylinder as protection against covert opening methods   Up to 20 additional side codes with integrated tampering control   Hardened steel elements as drilling protection                                      |
| Standards and guidelines                | EN 1303:2015 160B0C6D   90 minutes   ÖNORM<br>B5351: WZ6-BZ   BSI*   ČSN EN 1627 - Security class<br>4   Option VdS BZ(+)   Option SKG**   Option BSI***   |
| Technical installation situation        | For mortise locks according to DIN, ÖNORM, surface mounted locks and other devices suitable for the installation of Euro profile cylinder locks   Cam width 9.3 mm   |
| Included components                     | Cylinder lock with mounting screw M5   |
| Product code                            | M.[System].PZ.HZ-S.[Cylinder length on the outside A in mm].[Finish].[Option]  |
|   | EPS 5-pin half cylinder in Euro profile modular design,  |

<sup>&</sup>lt;sup>1</sup> EPS5 und EPS5M only

## **Dimensional drawing**



