

EPS Profile cylinder | Double cylinder Euro profile SY-MO



Product description

The EPS Euro profile double cylinder with modular design (SY-MO) is suitable for use in external and internal doors. The cylinder features external key override. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	27 ¹ 31 36 41 +5 ... total length ≥ 62 mm
Cylinder length on the inside I in mm	27 ¹ 31 36 41 +5 ... total length ≥ 62 mm
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	AS-A – Anti-Snap outer side KZ-[...] – Increased plug pulling and drilling protection SKG2-[...] – SKG ** certified VDS – VdS certified
Optional technical installation feature	BIF – Double cam Biffar® BL-[...] – blind cylinder FL1 – Free wheel function KS-[...] – Contact pin NS-[...] – Increased wear resistance SEW – Sea water protection SW-[...] – Dust and weather cover Z[...] – Cog wheel cam ZVS-[...] – Reduced cylinder body
Optional usage feature	BSZ – External key override TXT – Customer-specific text
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements Features in cylinder as protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Standards and guidelines	EN 1303:2015 160B0C6D 90 minutes ÖNORM B5351: WZ6-BZ BSI* ČSN EN 1627 - Security class 4 Option VdS BZ(+) Option SKG** Option BSI***
Technical installation situation	for mortise locks according to DIN, ÖNORM and surface mounted locks suitable for the installation of Euro profile cylinder locks Cam width 9.3 mm
Included components	Cylinder lock with mounting screw M5
Product code	M.[System].PZ.DZ-S.[Cylinder length on the outside A in mm/Cylinder length on the inside I in mm].[Finish].[Option]
Example	EPS 5-pin double cylinder with Euro profile, outside 31 mm, inside 36 mm, nickel finish, with BSZ option for external key override: M.EPS5.PZ.DZ-S.31/36.NI.BSZ

¹ EPS5 und EPS5M only

Dimensional drawing

