

# EPS Profile cylinder | Portal half cylinder



## Product description

The EPS Portal half cylinder in compact design is suitable for use in portal doors. It locks with an integrated bolt directly into the prepared socket without a rim lock. The cylinder can be locked from one side using the authorised keys. Potential applications are display cabinets and shop windows.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	31
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	NS-A – Increased wear resistance outside   SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text   VAR – VARIO
Accessories	Spray FinLube   Cylinder fixing screw
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   Features in cylinder as protection against covert opening methods   Up to 20 additional side codes with integrated tampering control   Hardened steel elements as drilling protection
Technical installation situation	For use in portal doors without rim lock
Included components	Cylinder lock without screws
Product code	M.[System].PZ.PHZ.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS Portal half cylinder 5-pin, length 31 mm, nickel finish, seawater protection optional: M.EPS5.PZ.PHZ.31.NI.SEW

## Dimensional drawing



