

4KS Cam lock | Cam lock 30 mm









Product description

The 4KS cam lock MB30 locks boxes and cabinets with a cam at the rear. It fits a hole pattern larger than 30 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are key boxes and mailboxes, display cases and technical distribution cabinets.

Technical information

Cylinder length on the outside A in mm	26
Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam ST[] – Locking direction A-H Z18 – Cogwheel cam Z18
Lever options	H[][A] – Cam for metal boxes and display cases HB[][A] – Cam for mail boxes
Optional usage feature	B01 – 2 key extracting positions 0°, 90° B03 – 2 key extracting positions 0°, -90° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear- controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Hole pattern larger than 30 mm flattened on the side rear mounted with a flat nut locking cam according to dimensional drawing for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder with fixing plate and standard cam H7233 or optionally mounted cam
Product code	M.4KS.HB.MB30.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS cam lock 30 mm diameter, nickel plated finish, length 26 mm, 2 key extracting positions at the bottom and left: M.4KS.HB.MB30.26.NI.B01

Dimensional drawing



