

4KS Profile cylinder | Half cylinder Swiss round profile SY-MO



Product description

The 4KS round profile half cylinder in modular design (SY-MO) is suitable for use in switch devices and in special technical doors. The cylinder can be locked from one side using an authorised key. Examples of applications are key switches for garage and roller doors as well as activation devices.

Technical information

Cylinder length on the outside A in mm	31 36 41 46 +5 ...
Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	FZG – Free wheel function for gear locks
Optional technical installation feature	BL-A – Blind outside KS-A – Contact pin outside SEW – Sea water protection SW-A – Dust and weather protection outside Z10 – Cogwheel cam Z10 Z18 – Cogwheel cam Z18
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube Cylinder fixing screw
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Standards and guidelines	90 minutes
Technical installation situation	For mortise locks, surface mounted locks and other devices which are suitable for the installation of round profile cylinder locks Cam width 8.5 mm Cam adjustable to 8 positions
Included components	Cylinder with fixing screw M5
Product code	M.4KS.PZ.RHZ-S.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS half cylinder in round profile, length 31 mm, nickel plated finish, with M4 thread option: M.4KS.PZ.RHZ-S.31.NI.2GW4

Dimensional drawing



