

4KS Cam lock | Mailbox cylinder 28 mm



Product description

The 4KS cam lock MB28ZB locks emergency key boxes and house mailbox systems with a cam on the rear. It fits a hole pattern larger than 28 mm and is fastened at the rear with a fixing plate and threaded pins. Further application examples are letter boxes and technical distribution cabinets.

Technical information

Cylinder length on the outside A in mm	27
Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam R050 – Escutcheon 50 mm ST[...] – Locking direction A-H SW-[...] – Dust and weather cover
Lever options	H[...] [A] – Cam for metal boxes and display cases HB[...] [A] – Cam for mail boxes
Optional usage feature	B01 – 2 key extracting positions 0°, 90° B03 – 2 key extracting positions 0°, -90° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Hole pattern larger than 28 mm use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder with fixing plate and standard cam H7233 or optionally mounted cam
Product code	M.4KS.HB.MB28ZB.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS cam lock 28 mm diameter, nickel plated finish, 2 key extracting positions at the bottom and left: M.4KS.HB.MB28ZB.27.NI.B01

Dimensional drawing



