

# 4KS Outside and inside cylinder | Outside cylinder 37 mm



## Product description

The 4KS outside cylinder AZ37.SEC is suitable for use on the outside of doors. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with rear pull-throughhole screws. As an example, they can be used in Scandinavian mortise locks.

## Technical information

Finish	NI – Nickel   MP – Polished brass   NPV – Nickel fully polished   MS – Brass   NP – Polished Nickel   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Cylinder length on the outside A in mm	31
Security features	Locking authorisation query in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling   4-fold screwed
Standards and guidelines	SS 3522 Category 3 <sup>1</sup>
Technical installation situation	Suitable for Scandinavian locks with high security requirements in combination with the IZ37.SEC   for 4-fold screw fastening on the rear side
Included components	Cylinder lock with tail bar
Product code	M.4KS.AI.AZ37.SEC.[Finish]
Example	4KS outside cylinder 40 mm diameter, nickel plated finish: M.4KS.AI.AZ37.SEC.NI

<sup>1</sup> In preparation

## Dimensional drawing

