

4KS Switch and switching cylinder | Switching cylinder 25 mm



Product description

The 4KS switching cylinder MB25 is suitable for use in key switches with several switch positions. It is equipped with configurable tail bar on the back, fits a hole pattern larger than 25 mm and is fastened on the inside by a flat nut or a fixing plate. Application examples are control panels and machine switches.

Technical information

Cylinder length on the outside A in mm	35
Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	SP[...] – Special tail bar
Optional usage feature	B[...] – 2 key extracting positions D04 – 4 key extracting positions 0°, 90°, 180°, 270° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in switches that are prepared for a compression fitting
Included components	Switching cylinder with tail bar as specified
Product code	M.4KS.SZ.MB25.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS switching cylinder MB25, length 35 mm, nickel plated finish, key removal at top and bottom: M.4KS.SZ.MB25.35.NI.B02

Dimensional drawing

