

FPS Profile cylinder | Portal double cylinder



Product description

The FPS Portal double cylinder in compact design is suitable for portal doors. It locks with an integrated bolt directly into the prepared socket without an rim lock. The cylinder can be locked on both sides using an authorised key. Potential applications are display cabinets and shop windows.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	31 36 41 +5 ...
Cylinder length on the inside I in mm	31 36 41 +5 ...
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	BL-[...] – blind cylinder SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For use in portal doors without rim lock
Included components	Cylinder lock without screws
Product code	M.[System].PZ.PDZ.[Outside cylinder length A in mm/Inside cylinder length I in mm]. [Surface].[Option]
Example	FPS Portal double cylinder 5-pin, outside 31 mm, inside 36 mm, nickel finish, with VARIO option: M.FPS5.PZ.PDZ.31/36.NI.VAR

Dimensional drawing



