

EPS Outside and inside cylinder | Outside cylinder 37 mm



Product description

The EPS outside cylinder AZ37.SEC is suitable for use on the outside of doors. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with rear throughhole screws. Potential applications are Scandinavian mortise locks.

Technical information

System	EPS6 – Extended Profile System 5 pin EPS6M – Extended Profile System Trademark protection 5 pin EPS7 – Extended Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	TAF-A – Temporary Access Function outside TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system with 6 or 7 active, spring-loaded locking elements Features in cylinder protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Standards and guidelines	EN 1303:2015 16-1-C62 SS 3522 Category 3
Technical installation situation	In combination with the IZ37.SEC, suitable for Scandinavian locks with high security requirements for 4-fold screw connection on the rear side
Included components	Cylinder lock with tail bar
Product code	M.[System].AI.AZ37.SEC.[Finish].[Option]
Example	EPS 5-pin outside cylinder, diameter 40 mm, nickel finish, with TAF: M.EPS5.AI.AZ37.SEC.NI.TAF-A

Dimensional drawing

