

4KS Cam lock | Cam lock 23 mm for mailboxes CH







Product description

The 4KS cam lock MB23CH locks boxes and display cabinets. It is equipped with a mount on the back for KABA® cam, suitable for letter boxes. It fits a hole pattern larger than 23 mm, is flattened on the underside and is fastened at the rear by a flat nut. Application examples are key boxes and letter boxes, display cabinets and technical distribution cabinets.

Technical information

Cylinder length on the outside A in mm	26
Finish	NI - Nickel MP - Polished brass NP - Polished Nickel MS - Brass ML - Brass lacquered CR - Chrome CP - Polished chrome PS - Patinated black PB - Patinated brown
Optional technical installation feature	0SN - Without cam SEW - Sea water protection ST[] - Locking direction A-H
Optional usage feature	B01 – 2 key extracting positions 0°, 90° B03 – 2 key extracting positions 0°, -90° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Hole pattern larger than 23 mm flattened on the underside rear mounted with a flat nut for use in mailboxes and other sheet metal cabinets
Included components	Cylinder lock with fastening nuts for cylinder and cam, also without cam, third-party cam on customer request
Product code	M.4KS.HB.MB23CH.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS cam lock, 23 mm diameter, nickel plated finish, length 26 mm, 2 key extracting positions at the bottom and left: M.4KS.HB.MB23CH.26.NI.B01

Dimensional drawing



