

# AIRKEY PADLOCK ANCHOR LAS 802-2WP GRADE 2



## PRODUCT INFORMATION

SYSTEM PROPERTY	
System type	electronic access systems   offline access systems   combined locking systems
Building type recommended	residential properties   residential complexes   residential buildings for communities   education   health care   industry and trade   office buildings   wholesale and retail   hotels and catering   cultural and leisure time   infrastructure

FUNCTION	
Media technology	JCOP
Function	event memory, last 1.000 events
Signals	acoustic   optical
Encryption	AES   encrypted data transfer
Interfaces	Bluetooth BLE   cable

USE	
Actuation	self-locking shackle   freely rotating outside thumb turn prevents tampering   lockable with access medium   engage only with authorisation
Installation situation	mesh gate   server cabinets   security fences   barrier systems   cellar cubicles   roller shutters
Humidity range	90% at 0°C
Ambient temperature	–20°C to +55°C
Opening cycles, battery set	30.000
Type of power supply	emergency power via programming interface   battery

MATERIAL

Material shackle	stainless steel door
------------------	----------------------

STANDARDS

Standard	SSF014 V3 Class 2   EN12320_2012 Grade 3
Directive	CE approved   IP65 ingress protection rating

ASSEMBLY

Assembly	special assembly tool required
Fixing	hook into eyelet or hasp
Design features	rated break point on outside thumb turn

INCLUDED COMPONENTS

Included components	padlock, 2 CR2 lithium batteries, assembly manual, Important information
---------------------	--

VARIANT

Padlock shackle	BDM08 – Shackle diameter 8 mm   N25 – Stainless steel shackle. Clearance 25 mm   N60 – Stainless steel shackle. Clearance 60 mm   N110 – Stainless steel shackle. Clearance 110 mm
-----------------	--

DIMENSIONAL DRAWING

