

EPS Outside and inside cylinder | Inside cylinder 37 mm



Product description

The EPS inside cylinder IZ37.SEC is suitable for use on the inside of the door. Cylinder is equipped with horizontal cam bar for mortise locks; it fits a hole pattern larger than 40 mm and is fixed with throughhole screws. Potential applications are Scandinavian mortise locks.

Technical information

System	EPS6 – Extended Profile System 5 pin EPS6M – Extended Profile System Trademark protection 5 pin EPS7 – Extended Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 6 or 7 active, spring-loaded locking elements Features in cylinder protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Technical installation situation	Suitable for Scandinavian locks in combination with AZ37.SEC for 4-fold screw connections on the rear
Included components	Cylinder lock with cylinder cover and cover plate screws
Product code	M.[System].AI.IZ37.SEC.[Finish].[Option]
Example	EPS 5-pin inside cylinder, diameter 40 mm, nickel finish, with VARIO re-coding function option: M.EPS5.AI.IZ37.SEC.NI.VAR

Dimensional drawing

