

ICS rim cylinder | AZ28.AZL



Product description

The ICS rim cylinder AZ28.AZL is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 28 mm and is secured on the rear side with eyelet screws. Application examples are LIPS® rim locks and surface mounted locks.

Technical information

Finish	NI – Nickel MS – Brass NP – Polished Nickel MP – Polished brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	FinLube spray
Security features	Locking authorisation request on 5 tracks 13 spring-loaded locking elements Durable length profile Specially shaped locking elements as scanning protection, bump key protection and picking protection Hardened HSS steel pins in the cylinder plug as drilling protection Steel balls in the body as drilling protection
Technical installation situation	For use in rim locks from other manufacturers up to door leaf thickness 56 mm
Included components	Cylinder lock with 2 M5x40 fixing screws
Product code	M.ICS.AI.AZ28.AZL.[Finish].[Option]
Example	ICS rim cylinder, diameter 28 mm, type AZL, nickel finish, with VARIO: M.ICS.AI.AZ28.AZL.NI.VAR

Dimensional drawing

