

## FPS Profile cylinder | Half cylinder Euro profile











## **Product description**

The FPS Euro profile half cylinder in compact design with 8-fold adjustable cam is suitable for use in switching devices and in special technical doors. The cylinder can be locked from one side using the authorised keys. Potential applications are key switches for garage doors, roller shutters and activation devices.

## **Technical information**

System	FPS5 - Functional Profile System 5 pin   FPS6 - Functional Profile System 6 pin
Cylinder length on the outside A in mm	271   31   36   41   +5
Finish	NI - Nickel   MS - Brass   NP - Polished Nickel   NPV - Nickel fully polished   MP - Polished brass   MPV - Brass fully polished   ML - Brass lacquered   CR - Chrome   CP - Polished chrome   CPV - Chrome fully polished   PS - Patinated black   PB - Patinated brown
Optional security features	FZG - Free wheel function for gear locks   KZ-A - Increased plug pulling and drilling protection outside   SKG2-[] - SKG ** certified   ZH-A - Hard metal plug pulling protection outside
Optional technical installation feature	2GW[] - Double rear fixing for HZ   BIF - Double cam Biffar®   FL1 - Free wheel function   KS-A - Contact pin outside   LW[] - Free travel   NS-A - Increased wear resistance outside   SEW - Sea water protection   SW-A - Dust and weather protection outside   Z[] - Cog wheel cam   ZVS-A - Reduced cylinder body outside
Optional usage feature	TXT - Customer-specific text   VAR - VARIO
Accessories	Spray FinLube   Cylinder fixing screw
Security features	Pin tumbler system cylinder with 5 or 6 active, spring- loaded locking elements   Features in the cylinder protect against covert opening methods   hardened steel elements for drilling protection
Standards and guidelines	FPS5 EN 1303:2015 160B0C4B   FPS6 EN 1303:2015 160B0C6B   90 minutes   ÖNORM B5351: WZ6-BZ   ČSN EN 1627 - Security class 3   Option SKG**
Technical installation situation	For mortise locks according to DIN, ÖNORM, rim locks and other devices suitable for the installation of Euro profile cylinder locks   Cam width 9.3 mm
Included components	Cylinder lock with mounting screw M5
Product code	M.[System].PZ.HZ.[Outside cylinder length A in mm].[Finish].[Option]

<sup>&</sup>lt;sup>1</sup> FPS5 only

## **Dimensional drawing**



