


# 4KS Switch and switching cylinder | Switching cylinder 29 mm EDP



## Product description

The 4KS switching cylinder AZ29SZ is suitable for use in various lift control systems. It is equipped with EDP tail bar on the back, fits a hole pattern larger than 29 mm with a 32 mm collar and is fastened through three M5 threaded holes on the back. Application examples are lift systems and escalators.

## Technical information

Cylinder length on the outside A in mm	23
Finish	NI – Nickel   MP – Polished brass   NPV – Nickel fully polished   MS – Brass   NP – Polished Nickel   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	B[...] – 2 key extracting positions   D04 – 4 key extracting positions 0°, 90°, 180°, 270°   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in key switches, prepared for EDP tail bars
Included components	Switching cylinder with EDP tail bar
Product code	M.4KS.SZ.AZ29SZ.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS switching cylinder AZ29, with EDP tail bar, nickel plated finish, key withdrawal at top and bottom: M.4KS.SZ.AZ29SZ.22.NI.B02

## Dimensional drawing

