

FPS Outside and inside cylinder | Mortise screw-in cylinder 30 mm



Product description

The FPS mortise screw-in cylinder AZ30RM is suitable for use on the outside of the door. It is equipped with cam for mortise locks, it fits an internal thread of 15/32" and is fastened by screwing it into the lock. Examples of applications are mortise locks.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	22 ¹ 25 ¹ 29 39 47 57 67
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam GLIP – For LIPS® cam GM0N – For Monarch® cam GYAL – For Yale® cam
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	Suitable for locks with screw-in fastening of the cylinder
Included components	Cylinder lock with Adams Rite® cam
Product code	M.[System].A1.AZ30RM.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS mortise screw-in cylinder 5-pin, length 25 mm, nickel finish, designed for LIPS® cam: M.FPS5.A1.AZ30RM.25.NI.GLIP

¹ FPS5 only

Dimensional drawing

