

4KS Outside and inside cylinder | Rim cylinder 28 mm



Product description

The 4KS rim cylinder AZ28.AZ1 is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface-mounted locks, fits a hole pattern larger than 32 mm and is secured on the rear side with throughhole screws. Application examples are LIPS® rim locks and surface mounted locks.

Technical information

Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in rim locks from other manufacturers up to door leaf thickness 56 mm
Included components	Cylinder lock with 2 M5x40 fixing screws
Product code	M.4KS.AI.AZ28.AZL.[Finish].[Option]
Example	4KS rim cylinder diameter 28 mm Type AZL, nickel plated finish with Vario: M.4KS.AI.AZ28.AZL.NI.VAR



Dimensional drawing

