


# FPS Outside and inside cylinder | Rim cylinder 25 mm



## Product description

The FPS rim cylinder AZ25.FP is suitable for use in garden gates. It is equipped with a tail bar for surface mounted locks, fits a hole pattern larger than 25 mm and is secured on the rear side with throughhole screws. Potential applications are garden gates with CISA® locks.

## Technical information

System	FPS5 – Functional Profile System 5 pin   FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Cylinder length on the outside A in mm	FPS5: 23   FPS6: 28
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements   Features in the cylinder protect against covert opening methods   hardened steel elements for drilling protection
Technical installation situation	For use on the outside, fastened from the rear using screws
Included components	Cylinder lock without screws, with tail bar and sleeve
Product code	M.[System].AI.AZ25.FP.[Finish].[Option]
Example	FPS 5-pin rim cylinder, diameter 25 mm, nickel finish, with VARIO re-coding function option: M.FPS5.AI.AZ25.FP.NI.VAR

## Dimensional drawing

