

# EPS Insert cylinder | Profile cylinder insert



## Product description

The EPS insert cylinder PZE.EK is suitable for use in conventional CISA® electric locks. It is provided with a cam bar mounted on the rear side and holes in the plug. Suitable for a hole pattern with a diameter of 17 mm and a 6 mm wide bar recess in the electric lock. Fastening takes place in the lock case.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	EPS5: 22   EPS6: 27   EPS5M: 22   EPS6M: 27
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	TXT – Customer-specific text   VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   up to 20 additional side codes with integrated manipulation control
Technical installation situation	Insert cylinder for the inner side of the "Elektrika" garden door strike.
Included components	Insert cylinder without fixing material
Product code	M.[System].EZ.PZE.EK.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin insert cylinder for the inner side of the garden door strike "Elektrika", length 22 mm, nickel finish, with re-coding function: M.EPS5.EZ.PZE.EK.22.NI.VAR

## Dimensional drawing

