

Akura 44 | Half cylinder Euro profile modular



Technical information

Cylinder lengths	27, 30, 35, ... + 5 mm
Finish	NI – Nickel MS – Brass CP – Polished chrome CPV – Chrome fully polished CR – Chrome ML – Brass lacquered MP – Polished brass MPV – Brass fully polished NP – Polished Nickel NPV – Nickel fully polished PB – Patinated brown PS – Patinated black
Optional security features	AS-A – Anti-Snap outer side FZG – Free wheel function for gear locks MAG – Magnetic copying protection VDS – VdS certified
Optional technical installation feature	2GW[...] – Double rear fixing for HZ LW[...] – Free travel NS-A – Increased wear resistance outside SEW – Sea water protection SW-A – Dust and weather protection outside Z[...] – Cogwheel
Optional usage feature	FZG – Free wheel function for gear locks LW[...] – Free travel SEW – Sea water protection TXT – Customer-specific text VAR – VARIO Z[...] – Cogwheel
Function	Can be locked with key Reversible key
Usage	technical doors tubular safes electronic key switch
Security	Pin rows: 3 Active pins: 6 Passive pins: 10 Drilling protection Pulling protection Picking protection Security card
Standards	EN 1303:2015 160B0C6B ČSN EN 1627, Security class 4 BSI* Fire resistance 90 minutes
Assembly	Mortise lock according to DIN, ÖNORM Modular design Cam width 9,3 mm Cam can be set to 8 positions
included components	Cylinder lock Fixing screw M5
Product code	M.A44.PZ.HZ-M.[Cylinder length].[Finish].[Options]

Dimensional drawing

