

FPS Profile cylinder | Scandinavian oval outside cylinder



Product description

The FPS Scandinavian oval outside cylinder is suitable for indoor and outdoor use. The cylinder can be locked from one side using the authorised keys. It is suitable for use with the Scandinavian internal cylinder. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

| | |
|---|--|
| System | FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin |
| Finish | NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown |
| Optional security features | KZ-A – Increased plug pulling and drilling protection outside |
| Optional technical installation feature | NS-A – Increased wear resistance outside SEW – Sea water protection |
| Optional usage feature | TXT – Customer-specific text VAR – VARIO |
| Accessories | Spray FinLube |
| Cylinder length on the outside A in mm | FPS5: 26 FPS6: 31 |
| Security features | Pin tumbler system cylinder with 5, 6 or 7 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection |
| Technical installation situation | For mortise locks, configured for Scandinavian cylinders For a higher security version with higher security category, see outside and inside cylinder AZ37.SEC |
| Included components | Cylinder lock without screws |
| Product code | M.[System].PZ.SKA.[Surface].[Length].[Option] |
| Example | FPS Scandinavian oval profile 5-pin outside cylinder, nickel plated and Temporary Access Function: M.FPS5.PZ.SKA.31.NI.TAF-A |

Dimensional drawing



