

4KS Profile cylinder | Double cylinder Swiss round profile SY-MO











Product description

The 4KS Euro profile double cylinder in modular design (SY-MO) is suitable for use in external and internal doors. The cylinder can be locked on both sides using an authorised key. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

Cylinder length on the outside A in mm	31 36 41 46 +5 Gesamtlänge ≥ 62 mm
Cylinder length on the inside I in mm	31 36 41 46 +5 Gesamtlänge ≥ 62 mm
Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	FZG – Free wheel function for gear locks
Optional technical installation feature	BL-[] – Blind cylinder KS-[] – Contact pin SEW – Sea water protection SW-[] – Dust and weather cover Z10 – Cogwheel cam Z10 Z18 – Cogwheel cam Z18
Optional usage feature	BSZ – External key override TXT – Customer-specific text
Accessories	Spray FinLube Cylinder fixing screw
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear- controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Standards and guidelines	90 minutes
Technical installation situation	For mortise locks and surface mounted locks suitable for the installation of round profile cylinder locks Cam width 8.5 mm
Included components	Cylinder with fixing screw M5
Product code	M.4KS.PZ.RDZ-S.[Outside cylinder length A in mm/Inside cylinder length I in mm]. [Finish].[Option]
Example	4KS double cylinder with round profile, outside 31 mm, inside 36 mm, nickel plated finish, with option BSZ lockable both sides: M.4KS.PZ.RDZ-S.31/36.NI.BSZ

Dimensional drawing



