


EPS Switch and switching cylinder | Switch cylinder 19 mm SY-MO with switch



Product description

The EPS switch cylinder MB 19SZ-S is suitable for direct integration into circuits. It is equipped with a microswitch on the rear, fits a hole pattern larger than 19 mm and is flattened on the side (anti-twist device). It is fastened on the inside by a flat nut. Application examples are control panels and machine switches.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	19
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	B01 – 2 key extracting positions 0°, 90° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements up to 20 additional side codes with integrated manipulation control
Technical installation situation	Possible switching capacities: 250 VAC. 5A 125 VAC: 5A 0–15 VDC: 5A 15–30 VDC: 3A
Included components	Switch cylinder with integrated microswitch
Product code	M. [System].SZ.MB19SZ-S.39. [Finish].[Option]
Example	EPS 5-pin switch cylinder, diameter 19 mm, nickel finish, with 2 key extracting positions: M.EPS5.SZ.MB19SZ-S.19.NI.B01

Dimensional drawing

