

# 4KS Switch and switching cylinder | Lift cylinder 22 mm



## Product description

The 4KS switching cylinder MR22AF is suitable for use in various key switches. It is equipped with configurable tail bar on the back. It fits a hole pattern larger than 22 mm and is fastened by 2 rear screws. Examples of applications are alarm systems, escalators and control units.

## Technical information

Cylinder length on the outside A in mm	35
Finish	NI – Nickel   MP – Polished brass   NPV – Nickel fully polished   MS – Brass   NP – Polished Nickel   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	BEFE – Fixing plate square   BEFR – Fixing plate round   SP[...] – Special tail bar
Optional usage feature	D04 – 4 key extracting positions 0°, 90°, 180°, 270°   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	When selecting the switching cylinder, it must be ensured that the switch angle of the cylinder matches that of the switch
Included components	Switching cylinder with tail bar as specified
Product code	M.4KS.SZ.MR22AF.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS switching cylinder MR22, length 35 mm, nickel plated finish, key removal at top and bottom: M.4KS.SZ.MR22AF.35.NI.B02

## Dimensional drawing

