

FPS Outside and inside cylinder | Inside cylinder 37 mm



Product description

The FPS inside cylinder IZ37.SEC is suitable for use on the inside of the door. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with pull-throughhole screws. Potential applications are Scandinavian mortise locks.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	Suitable for Scandinavian locks in combination with AZ37.SEC for 4-fold screw connections on the rear
Included components	Cylinder lock with cylinder cover and cover plate screws
Product code	M.[System].AI.IZ37.SEC.[Finish].[Option]
Example	FPS Inside cylinder 5-pin, diameter 37 mm, nickel finish, with VARIO re-coding function option: M.FPS5.AI.IZ37.SEC.NI.VAR



Dimensional drawing

