

ICS cam lock | MB28ZB







Product description

The ICS cam lock MB28ZB locks emergency key boxes and house mailbox systems with a cam on the rear. It fits a hole pattern larger than 28 mm and is fastened at the rear with a fixing plate and threaded pins. Further application examples are letter boxes and technical distribution cabinets.

Technical information

Cylinder length on the outside A in mm	27
Finish	NI - Nickel MS - Brass NP - Polished Nickel MP - Polished brass ML - Brass lacquered CR - Chrome CP - Polished chrome PS - Patinated black PB - Patinated brown
Optional technical installation feature	R050 - Escutcheon 50 mm ST[] - Locking direction A-H SW-A - Dust and weather protection outside
Lever options	H[][A] – Cam for metal boxes and display cases HB[][A] – Cam for mail boxes
Optional usage feature	B01 – 2 key extracting positions 0°, 90° B03 – 2 key extracting positions 0°, -90°
Accessories	Spray FinLube
Security features	Locking authorisation request on up to 5 tracks Up to 13 spring-loaded locking elements Durable length profile Specially shaped locking pins as scanning protection and picking protection Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	For use in key and mailboxes and other metal cabinets
Included components	Cylinder lock with assembled fixing plate and standard cam H7233 or optional cam
Product code	M.ICS.HB.MB28ZB.[Outside cylinder length A in mm].[Finish].[Option]
Example	ICS cam lock 28 mm diameter, nickel finish, 2 key extracting positions at the bottom and left: M.ICS.HB.MB28ZB.27.NI.B01

Dimensional drawing

