

# FPS Outside and inside cylinder | Rim cylinder 29 mm



## Product description

The FPS rim cylinder AZ29.I063 is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 29 mm and is secured on the rear side with throughhole screws. Potential applications are rim locks and surface mounted s.

## Technical information

System	FPS5 – Functional Profile System 5 pin   FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	API63 – Fixing plate IKON® 4063   R01 – Escutcheon IKON®
Door leaf thickness options	TS56 – Door thickness 46 up to 56 mm   TS66 – Door thickness 57 up to 66 mm   TS76 – Door thickness 67 up to 76 mm   TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements   Features in the cylinder protect against covert opening methods   hardened steel elements for drilling protection
Technical installation situation	For use in IKON® rim locks up to door leaf thickness 45 mm
Included components	With tail bar and 2 M6×28 fastening screws
Product code	M.[System].AI.AZ29.I063.[Finish].[Option]
Example	FPS rim cylinder 5-pin for IKON® rim locks type 63, nickel finish with VARIO re-coding function option: M.FPS5.AI.AZ29.I063.NI.VAR

## Dimensional drawing

