

# EPS Cam lock | Cam lock 22 mm for Kirner®



## Product description

The EPS cam lock MB22K locks the locking linkage of boxes and cabinets with a rear 8 mm square spindle. It fits a hole pattern larger than 22 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are lockers and metal cabinets.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	27 <sup>1</sup>   32   37
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	GKGT – Door knob 38 mm for glass doors   SR22 – Dust and weather protection cover   ST[...] – Locking direction A-H
Optional usage feature	B[...] – 2 key extracting positions   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   up to 20 additional side codes with integrated manipulation control
Technical installation situation	Hole pattern larger than 22 mm flattened on the side   rear mounted with a flat nut   for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock with fixing nuts for cylinder and cam; also without cam
Product code	M.[System].HB.MB22K <sup>2</sup> . [Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin cam lock 22 mm diameter, length 27 mm, nickel finish, 2 key extracting positions at the bottom and left: M.EPS5.HB.MB22K.27.NI.B01

<sup>1</sup> Only EPS5 and EPS5M; <sup>2</sup> can also be ordered in modular design (SY-MO) MB22K-S

## Dimensional drawing

