

FPS Profile cylinder | Half cylinder UK oval profile



Product description

The FPS UK half cylinder in compact design with 8-way adjustable cam is suitable for use in switching devices and in special doors with a suitable UK oval profile lock. The cylinder can be locked from one side using the authorised keys. Potential applications are key switches for garage doors, roller shutters and activation devices.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	31 36 41 +5 ...
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	BL-[...] – blind cylinder FL1 – Free wheel function SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For mortise locks with UK oval profile Cam width 9.0 mm
Included components	Cylinder lock with mounting screw M5
Product code	M.[System].PZ.0HZ.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS 5-pin oval profile half cylinder, length 31 mm, nickel finish, seawater protection optional: M.FPS5.PZ.0HZ.31.NI.SEW

Dimensional drawing

