

Akura 44 | Rim cylinder 28 mm



Technical information

Finish	NI – Nickel MS – Brass CP – Polished chrome CPV – Chrome fully polished CR – Chrome ML – Brass lacquered MP – Polished brass MPV – Brass fully polished NP – Polished Nickel NPV – Nickel fully polished PB – Patinated brown PS – Patinated black
Optional security features	-
Optional technical installation feature	APA – Fixing plate ABUS® GWB6 – 1 thread M6 R050 – Escutcheon 50 mm R060 – Escutcheon 60 mm R0A – Escutcheon ABUS® R0I – Escutcheon IKON® TS[...] – Door thickness
Optional usage feature	APA – Fixing plate ABUS® R050 – Escutcheon 50 mm R060 – Escutcheon 60 mm R0A – Escutcheon ABUS® R0I – Escutcheon IKON® TS[...] – Door thickness TXT – Customer-specific text VAR – VARIO
Function	Can be locked with key Reversible key
Usage	apartment entrance
Security	Pin rows: 3 Active pins: 6 Passive pins: 10 Security card
Standards	-
Assembly	For various rim locks Rear fixing with screws Hole pattern d > 28 mm
included components	Cylinder lock 2 mounting screws M5x40
Product code	M.A44.AI.AZ28.AZI.[Finish].[Options]

Dimensional drawing

