

FPS Outside and inside cylinder | Rim cylinder 28 mm



Product description

The FPS rim cylinder AZ28.AZL is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 28 mm and is secured on the rear side with throughhole screws. Application examples are LIPS® rim locks and surface mounted s.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Cylinder length on the outside A in mm	FPS5: 22 FPS6: 27
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For use in supplementary locks from other manufacturers up to door leaf thickness 56 mm
Included components	Cylinder lock with 2 M5x40 fixing screws
Product code	M.[System].AI.AZ28.AZL.[Surface].[Option]
Example	FPS rim cylinder 5-pin, diameter 28 mm, type AZL, nickel finish, with VARIO re-coding function option: M.FPS5.AI.AZ28.AZL.NI.VAR

Dimensional drawing

