

FPS Cam lock | Cam lock 26 mm



Product description

The FPS cam lock MB26 locks boxes and display cabinets with a locking cam at the rear. It fits a hole pattern larger than 26 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are key boxes and mailboxes, display cases and technical distribution cabinets.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	27 ¹ 32 37
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam ST[...] – Locking direction A-H
Lever options	H[...]A] – Cam for metal boxes and display cases HB[...]A] – Cam for mail boxes
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	Hole pattern larger than 26 mm flattened on the side rear mounted with a flat nut locking cam according to dimensional drawing for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.[System].HB.MB26.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS 5-pin cam lock, diameter 26 mm, length 27 mm, nickel finish, 2 key extracting positions at the bottom and left: M.FPS5.HB.MB26.27.NI.B01

¹ FPS5 only

Dimensional drawing

