

## 4KS Outside and inside cylinder | Rim cylinder 28 mm



### Product description

The 4KS rim cylinder AZ28.AZI is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 28 mm and is secured on the rear side with throughhole screws. Application examples are rim locks and surface mounted locks.

### Technical information

Finish	NI – Nickel   MP – Polished brass   NP – Polished Nickel   MS – Brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional security features	KZ-A – Increased plug pulling and drilling protection outside   SKG3-A – SKG *** certified outside
Optional technical installation feature	APA – Fixing plate ABUS®   GWB6 – 1 thread M6   R0A – Escutcheon ABUS®   R0SKG – Escutcheon SKG
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm   TS76 – Door thickness 67 up to 76 mm   TS86 – Door thickness 77 up to 86 mm
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Standards and guidelines	Option SKG***
Technical installation situation	In combination with ABUS® rim locks up to door leaf thickness 56 mm
Included components	Cylinder with 2 M5×40 fixing screws (optional GWB6 M6×40)
Product code	M.4KS.AI.AZ28.AZI.[Finish].[Option]
Example	4KS rim cylinder for ABUS rim locks, nickel plated finish with fixing plate: M.4KS.AI.AZ28.AZI.NI.APA

### Dimensional drawing



