

EPS Profile cylinder | Scandinavian oval inside cylinder





Product description

The EPS Scandinavian oval inside cylinder is suitable for use in external and internal doors. The cylinder can be locked from one side using the authorised keys. It is suitable for use with the Scandinavian outside cylinder. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin EPS7 – Extended Profile System 7 pin
Finish	NI - Nickel MS - Brass NP - Polished Nickel NPV - Nickel fully polished MP - Polished brass MPV - Brass fully polished ML - Brass lacquered CR - Chrome CP - Polished chrome CPV - Chrome fully polished PS - Patinated black PB - Patinated brown
Optional security features	KZ-I - Increased plug pulling and drilling protection inside
Optional technical installation feature	NS-I – Increased wear resistance inside SEW – Sea water protection
Optional usage feature	TXT - Customer-specific text VAR - VARIO
Accessories	Spray FinLube
Cylinder length on the outside A in mm	EPS5, EPS5M: 26 EPS6, EPS6M, EPS7: 31
Security features	Pin tumbler system with 5, 6 or 7 active spring-loaded locking elements features in cylinder as protection against covert opening methods up to 20 additional side codes with integrated tampering control hardened steel elements as drilling protection
Technical installation situation	For mortise locks, configured for Scandinavian cylinders For a higher security version with higher security category, see outside and inside cylinder IZ37-K.SEC
Included components	Cylinder lock with 2 M5x40 fixing screws
Product code	M.[System].PZ.SKI.[Cylinder length on the outside A in mm].[Finish]
Example	EPS Scandinavian oval profile inside cylinder 5-pin, nickel finish: M.EPS5.PZ.SKI.31.NI