

EPS Outside and inside cylinder | Mortise screw-in cylinder 30 mm



Product description

The EPS mortise screw-in cylinder AZ30RM is suitable for use on the door outside. It is equipped with cam for mortise locks, it fits an internal thread of 1 5/32" and is fastened by screwing it into the lock. Application examples are mortise locks.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	22 ¹ 25 ¹ 29 39 47 57 67
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam GLIP – For LIPS® cam GM0N – For Monarch® cam GYAL – For Yale® cam
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements Features in cylinder as protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Technical installation situation	Suitable for locks with screw-in fastening of the cylinder
Included components	Cylinder locks with Adams Rite® cam
Product code	M.[System].AI.AZ30RM ² . [Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS mortise screw-in cylinder 5-pin mortise, length 25 mm, nickel finish, designed for LIPS® cam: M.EPS5.AI.AZ30RM.25.NI.GLIP

¹ Only EPS5 and EPS5M; ² can also be ordered in modular design (SY-MO) MB22K-S

Dimensional drawing

