

AIRKEY PADLOCK WITH MODULE, CLEARANCE WIDTH 24 MM



PRODUCT INFORMATION

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SYSTEM PROPERTY | |
| System specification | Online administration Easy to use and operate |
| System type | electronic access systems offline access systems combined locking systems |
| Building type recommended | residential properties residential complexes residential buildings for communities education health care industry and trade office buildings wholesale and retail hotels and catering cultural and leisure time infrastructure |

| | |
|------------------|---------------------------------------|
| FUNCTION | |
| Media technology | JCOP |
| Function | event memory, last 1.000 events |
| Signals | acoustic optical |
| Encryption | AES ECDSA encrypted data transfer |
| Interfaces | Bluetooth BLE cable |

| | |
|------------------------|----------------------------------------------------------------------------------------------------------------------|
| USE | |
| Actuation | freely rotating outside thumb turn prevents tampering lockable with access medium engage only with authorisation |
| Design feature | elegant design without compromise timeless |
| Installation situation | mesh gate server cabinets security fences barrier systems cellar cubicles roller shutters chain barriers |
| Humidity range | 90% at 0°C |

USE

| | |
|-----------------------------|-----------------------------------------------------|
| Ambient temperature | –20°C to +55°C |
| Opening cycles, battery set | 30.000 |
| Type of power supply | emergency power via programming interface battery |

MATERIAL

| | |
|------------------|----------------|
| Material shackle | hardened steel |
|------------------|----------------|

STANDARDS

| | |
|-----------|-----------------------------------------------------------|
| Standard | EN 1634-1 90 minutes Austrian Standard 3859: 90 minutes |
| Directive | CE approved |

ASSEMBLY

| | |
|-----------------|-----------------------------------------|
| Assembly | special assembly tool required |
| Design | modular system SY-MO |
| Fixing | hook into eyelet or hasp |
| Design features | rated break point on outside thumb turn |

INCLUDED COMPONENTS

| | |
|---------------------|--------------------------------------------------------------------------|
| Included components | padlock, 2 CR2 lithium batteries, assembly manual, Important information |
|---------------------|--------------------------------------------------------------------------|

VARIANT

| | |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Finish | NI – Nickel |
| Padlock shackle | N30 – Stainless steel shackle. Clearance 30 mm N40 – Stainless steel shackle. Clearance 40 mm N50 – Stainless steel shackle. Clearance 50 mm N60 – Stainless steel shackle. Clearance 60 mm N70 – Stainless steel shackle. Clearance 70 mm N80 – Stainless steel shackle. Clearance 80 mm N90 – Stainless steel shackle. Clearance 90 mm N100 – Stainless steel shackle. Clearance 100 mm N120 – Stainless steel shackle. Clearance 120 mm N150 – Stainless steel shackle. Clearance 150 mm N180 – Stainless steel shackle. Clearance 180 mm N200 – Stainless steel shackle. Clearance 200 mm S17 – Steel shackle. Clearance 17 mm S30 – Steel shackle. Clearance 30 mm |

OPTION

| | |
|----------------|-------------------------------------------|
| Padlock option | BS – Shackle protection RL – Drain hole |
|----------------|-------------------------------------------|

DIMENSIONAL DRAWING

