

# 4KS Switch and switching cylinder | Rim cylinder 29 mm



## Product description

The 4KS switching cylinder SZ29 is suitable for use in key switches with several switch positions. It is equipped with configurable tail bar on the rear. Suitable for a hole pattern larger than 29 mm, terminating at the front with a 32 mm collar. It is fastened with two M5 threaded holes on the rear. Examples of applications are alarm systems, escalators and control units.

## Technical information

Cylinder length on the outside A in mm	33
Finish	NI – Nickel   MP – Polished brass   NPV – Nickel fully polished   MS – Brass   NP – Polished Nickel   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	SP[...] – Special tail bar
Optional usage feature	B[...] – 2 key extracting positions   D04 – 4 key extracting positions 0°, 90°, 180°, 270°   F06 – 6 key extracting positions 0°, 60°, 120°, 180°, 240°, 300°   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in key switches
Included components	Switching cylinder
Product code	M.4KS.SZ.AZ29.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS switching cylinder SZ29, length 33 mm, nickel plated finish, key removal from top and bottom: M.4KS.SZ.AZ29.33.NI.B02

## Dimensional drawing



