

# FPS Switch and switching cylinder | Lift cylinder 28 mm




### Product description

The FPS Lift cylinder MR28A is suitable for use in various lift control systems. It has no rear side cam bar, is suitable for a hole pattern larger than 28 mm, and is fastened by two screws at the rear. Application examples are lift systems and escalators.

### Technical information

System	FPS5 – Functional Profile System 5 pin   FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	26 <sup>1</sup>   31
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	For use in lifts or lift controls with a hole pattern larger than 28 mm
Included components	Lift cylinder without cam bar
Product code	M.[System].SZ.MR28A.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS Lift cylinder 5-pin, diameter 28 mm, length 26 mm, nickel finish: M.FPS5.SZ.MR28A.26.NI



### Dimensional drawing

