

4KS Profile cylinder | Scandinavian oval outside cylinder



Product description

The 4KS Scandinavian outside cylinder is suitable for use in outside and inside doors. The cylinder can be locked from one side using an authorised key. It is suitable for use with the Scandinavian oval inside cylinder. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Standards and guidelines	EN 1303:2015 160B0C6D SS 3522 Category 3 ¹
Technical installation situation	For mortise locks, configured for Scandinavian cylinders Cylinder for a higher security with higher security category, see outside and inside cylinder AZ37.SEC
Included components	Cylinder lock without screws
Product code	M.4KS.PZ.SKA.31.[Finish]
Example	4KS Scandinavian oval profile outside cylinder, nickel plated finish: M.4KS.PZ.SKA.31.NI

¹ In preparation

Dimensional drawing

