

# ICS rim cylinder | AZ29.I050



## Product description

The ICS AZ29.I050 rim cylinder is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface-mounted locks, fits a hole pattern larger than 29 mm and is secured on the rear side with throughhole screws. Potential applications are rim locks and surface mounted locks.

## Technical information

Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   MP – Polished brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	R01 – Escutcheon IKON®
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm   TS76 – Door thickness 67 up to 76 mm   TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Locking authorisation request on 5 tracks   13 spring-loaded locking elements   Durable length profile   Specially shaped locking elements as scanning protection, bump key protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection   Steel balls in the body as drilling protection
Technical installation situation	For use in IKON® rim locks up to door leaf thickness 56 mm
Included components	With tail bar and 2 M5×40 fixing screws
Product code	M.ICS.AI.AZ29.I050.[Finish].[Option]
Example	ICS rim cylinder for Ikon rim locks type 50, nickel finish with Vario: M.ICS.AI.AZ29.I050.NI.VAR

## Dimensional drawing

