

Akura 44 | Scandinavian oval outside cylinder





Technical information

Finish NI - Nickel MS - Brass CP - Polished chrome CPV - Chrome fully polished CR - Chrome ML - Brass lacquered MP - Polished brass MPV - Brass fully polished NP - Polished Nickel NPV - Nickel fully polished PB - Patinated brown PS - Patinated black Optional security features MAG - Magnetic copying protection Optional usage feature TXT - Customer-specific text VAR - VARIO Function Can be locked with key Reversible key Usage door exterior connecting doors entrance doors apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks Cylinder lock Product code M.A44.PZ.SKA.[Cylinder length].[Finish].[Options]	Cylinder lenghts	30 mm
Optional technical installation feature Optional usage feature TXT - Customer-specific text VAR - VARIO Function Can be locked with key Reversible key Usage door exterior connecting doors entrance doors apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	Finish	lacquered MP - Polished brass MPV - Brass fully polished NP - Polished Nickel NPV - Nickel fully
feature Optional usage feature TXT - Customer-specific text VAR - VARIO Function Can be locked with key Reversible key Usage door exterior connecting doors entrance doors apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	Optional security features	MAG - Magnetic copying protection
Function Can be locked with key Reversible key Usage door exterior connecting doors entrance doors apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	•	-
Usage door exterior connecting doors entrance doors apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	Optional usage feature	TXT - Customer-specific text VAR - VARIO
apartment entrance metal frame door security doors Security Pin rows: 3 Active pins: 6 Drilling protection Pulling protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	Function	Can be locked with key Reversible key
protection Picking protection Security card Standards EN 1303:2015 160B0C6B Fire resistance 90 minutes Assembly For Scandinavian mortise locks included components Cylinder lock	Usage	, , , , , , , , , , , , , , , , , , , ,
Assembly For Scandinavian mortise locks included components Cylinder lock	Security	, , , , , ,
included components Cylinder lock	Standards	EN 1303:2015 160B0C6B Fire resistance 90 minutes
	Assembly	For Scandinavian mortise locks
Product code M.A44.PZ.SKA.[Cylinder length].[Finish].[Options]	included components	Cylinder lock
	Product code	M.A44.PZ.SKA.[Cylinder length].[Finish].[Options]

Dimensional drawing

