

# 4KS Switch and switching cylinder | Switch cylinder 19 mm with switch



### Product description

The 4KS switch cylinder MB19SZ is suitable for direct integration into circuits. It is equipped with a microswitch on the rear, fits a hole pattern larger than 19 mm and is flattened on the side (to prevent rotation). It is fastened on the inside by a flat nut. Application examples are control panels and machine switches.

### Technical information

Cylinder length on the outside A in mm	39
Finish	NI – Nickel   MP – Polished brass   NPV – Nickel fully polished   MS – Brass   NP – Polished Nickel   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	B01 – 2 key extracting positions 0°, 90°   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Possible switching capacities: 50 VAC: 5 A   0–15 VDC: 5 A   15–30 VDC: 3 A   250 VAC, 5 A
Included components	Switch cylinder with integrated microswitch, fastening nut M19
Product code	M.4KS.SZ.MB19SZ.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS Switch cylinder, 19 mm diameter, nickel plated finish, with 2 key extracting positions: M.4KS.SZ.MB19SZ.39.NI.B01

### Dimensional drawing



