

EPS Outside and inside cylinder | Rim cylinder 29 mm I063



Product description

The EPS AZ28.AZI rim cylinder is suited for use on the outside of the door. Surface mounted lock equipped with a horizontal locking bar, fits a hole pattern larger than 29 mm and is secured on the rear side with throughhole screws. Potential applications are rim locks and surface mounted locks.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	API63 – Fixing plate IKON® 4063 R01 – Escutcheon IKON®
Door leaf thickness options	TS56 – Door thickness 46 up to 56 mm TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements Features in cylinder as protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Technical installation situation	For use in IKON® rim locks up to door leaf thickness 45 mm
Included components	With tail bar and 2 M6×28 fastening screws
Product code	M.[System].AI.AZ29.I063.[Finish].[Option]
Example	EPS rim cylinder 5-pin for IKON® rim locks type 63, nickel finish with VARIO re-coding function option: M.EPS5.AI.AZ29.I063.NI.VAR

Dimensional drawing



