

FPS Outside and inside cylinder | Rim cylinder 28 mm



Product description

The FPS AZ28.AZI rim cylinder is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 28 mm and is secured on the rear side with throughhole screws. Application examples are rim locks and surface mounted.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	SKG2-A – SKG ** certified outside
Optional technical installation feature	APA – Fixing plate ABUS® GWB6 – 1 thread M6 R0A – Escutcheon ABUS® R0SKG – Escutcheon SKG
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Cylinder length on the outside A in mm	FPS5: 21 FPS6: 26
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	In combination with ABUS® rim locks up to door leaf thickness 56 mm
Included components	Cylinder lock with 2 M5×40 fastening screws (with GWB6 M6×40 option)
Product code	M.[System].AI.AZ28.AZI.[Surface].[Option]
Example	FPS rim cylinder 5-pin for ABUS rim locks, nickel finish with M6 holes: M.FPS5.AI.AZ28.AZI.NI.GWB6

Dimensional drawing



