

ICS Padlock | HM24-S



Product description

The ICS padlock HM24-S with hardened steel shackle is suitable for securing doors or objects that are equipped with hasps or eyelets. Examples of applications are roller shutters, barrier systems, chain fastenings and barrier fences.

Technical information

| | |
|--|---|
| Niro/steel shackle variant, clear height in mm | S17 S30 N30 N40 N50 N60 N70 N80 N90 N100 N120 N150 N180 N200 |
| Finish | NI – Nickel |
| Optional security features | BS – Shackle protection |
| Optional technical installation feature | SW-A – Dust and weather protection outside |
| Optional usage feature | VAR – VARIO |
| Accessories | Spray FinLube |
| Security features | Locking authorisation request on 5 tracks 13 spring-loaded locking elements Durable length profile Specially shaped locking elements as scanning protection, bump key protection and picking protection Hardened HSS steel pins in the cylinder plug as drilling protection Hardened steel ball and 1st tumbler made of hardened steel as drilling protection |
| Included components | Padlock |
| Product code | M.ICS.HA.HM24-S.[S/N clear height in mm].[Finish].[Option] |
| Example | ICS padlock HM24-S, with stainless steel shackle, clearance height of 50 mm, nickel finish, with dust and weather protection: M.ICS.HA.HM24-S-S.N50.NI.SW-A |

Dimensional drawing

