


4KS Switch and switching cylinder | Lift cylinder 28 mm



Product description

The 4KS lift cylinder MR28A is suitable for use in various lift control systems. It has no rear side cam bar, is suitable for a hole pattern larger than 28 mm, and is fastened by two screws at the rear. Application examples are lift systems and escalators.

Technical information

Cylinder length on the outside A in mm	27 32
Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in lifts or lift controls with a hole pattern larger than 28 mm
Included components	Lift cylinder without cam bar
Product code	M.4KS.SZ.MR28A.[Outside cylinder length A in mm].[Finish]
Example	4KS lift cylinder 28 mm, nickel plated finish, length 32 mm: M.4KS.SZ.MR28A.32.NI

Dimensional drawing

