

# 4KS Padlock | Padlock with module, clearance width 24 mm



## Product description

The 4KS padlock with hardened steel shackle is suitable for securing doors or objects fitted with a hasp or eyelet. Examples of applications are roller shutters, barrier systems, chain fastenings and barrier fences.

## Technical information

|  |  |
|--|--|
| Niro/steel shackle variant, clear height in mm | S17   S30   N30   N40   N50   N60   N70   N80   N90   N100   N120   N150   N180   N200   |
| Finish   | NI – Nickel  |
| Optional security features                     | BS – Shackle protection  |
| Optional technical installation feature        | SW-A – Dust and weather protection outside   |
| Optional usage feature                         | TXT – Customer-specific text   |
| Accessories                                    | Spray FinLube  |
| Security features                              | Locking authorisation request in at least 18 request positions (authorisation positions)   12 springless, linearly controlled locking pins   Hard metal or hardened steel safety elements to prevent drilling and pulling   Brass connecting rod to prevent it from being torn off   Two-way locking of the security bar   Key can only be removed when closed |
| Included components                            | Padlock  |
| Product code                                   | M.4KS.HA.HM24-S.[S/N clear height in mm].[Finish].[Option]   |
| Example  | 4KS padlock HM24-S, with stainless steel shackle, clearance height of 50 mm, nickel plated finish, with dust and weather protection: M.4KS.HA.HM24-S.N50.NI.SW-A   |



## Dimensional drawing

