

# ICS cam lock | MB22



## Product description

The ICS cam lock MB22 locks boxes and cabinets with a cam at the rear. It is suitable for a hole pattern larger than 22 mm, is flattened on the side and fastened at the rear by a flat nut. Application examples are key boxes and letter boxes, display cabinets and technical distribution cabinets.

## Technical information

Cylinder length on the outside A in mm	27   32   37
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   MP – Polished brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	GKGT – Door knob 38 mm for glass doors   GTA[...] – Glass door plate wide   GTB[...] – Glass door plate high   SR22 – Dust and weather protection cover   ST[...] – Locking direction A-H
Lever options	H[...]A] – Cam for metal boxes and display cases   HB[...]A] – Cam for mail boxes
Optional usage feature	B01 – 2 key extracting positions 0°, 90°   B03 – 2 key extracting positions 0°, -90°
Accessories	Spray FinLube   Door knob 38 mm for glass and furniture doors
Security features	Locking authorisation request on up to 5 tracks with spring-loaded locking elements   Durable length profile   Specially shaped locking pins as scanning protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	Hole pattern larger than 22 mm flattened on the side   rear mounted with a flat nut   locking cam according to dimensional drawing   for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.ICS.HB.MB22.[Outside cylinder length A in mm].[Finish].[Option]
Example	ICS cam lock 22 mm diameter, nickel finish, length 27 mm, 2 key extracting positions at the bottom and left: M.ICS.HB.MB22.27.NI.B01

## Dimensional drawing

