

# ICS Coin operated lock cylinder | DPM25



## Product description

The ICS cam lock DPM25 locks coin operated locks with a flattened core end on the side. It fits a hole pattern larger than 25 mm, is flattened on the side and is secured in the lock by a flat nut. Application examples are coin operated locks.

## Technical information

Cylinder length on the outside A in mm	37
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   MP – Polished brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	DPM[...] – Coin operated lock Depomat®   LI – Left   RE – Right
Accessories	Spray FinLube
Security features	Locking authorisation request on up to 5 tracks with spring-loaded locking elements   Durable length profile   Specially shaped locking pins as scanning protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	In combination with a Depomat coin operated lock
Included components	Coin operated lock cylinder
Product code	M.ICS.HB.DPM25.[Outside cylinder length A in mm].[Option]
Example	ICS coin operated lock cylinder diameter 25 mm, nickel finish on right-hand side: M.ICS.HB.DPM25.NI.RE



## Dimensional drawing

